



AL2304-111

Symbol	Description	Part Number	Sug. Ret.
C101, 102, 103, 104, 111, 112	Sintered Aluminum, 0.33UF, 25V	CS22340-3	.45
C105, 106, 121, 122, 123, 124	Tantalum, 4UF, 35V	CL22305-14	.80
C107, 108, 109, 110	Tantalum, 1UF, 35V	CL22305-3	.60
C113, 114, 115, 116	Ceramic, 820pF, 10%, 50V	CK22347-11	.30
C117, 118, 119, 120	Sintered Aluminum, 1UF, 25V	CS22340-5	.45
I9, 10	Lamp, Sub-Miniature	LM21421-4	.70
L101, 102	Choke, 39mH	L50334-11	1.05
PC101, 102, 103, 104	Encapsulated Circuit	EP50187-87	1.60
Q101, 102, 103, 104	Transistor, NPN (BC414C)	TR01015	.85
Q105, 106, 107, 108	Transistor NPN (BC414B)	TR01015-2	1.15
R81, 82, 83, 84	22K	RF25DC223J	.30
R85, 86, 87, 88, 89, 90, 91, 92	56K	RF25DC563J	.30
R101, 102, 103, 104	2.2K	RF25DC222J	.30
R105, 106, 107, 108	270K	RF25DC274J	.30
R109, 110, 111, 112	82K	RF25DC823J	.30
R113, 114, 115, 116	1.8K	RF25DC182J	.30
R117, 118, 119, 120	1K	RF25DC102J	.30
R124A, B	Potentiometer, 20K Dual-Slide	RP50160-286	3.00
R126, 127	330	RF25DC331J	.30
R128, 129, 130, 131	1M	RF25DC105J	.30
R132A, B, 133A, B, 138A, B, 139A, B	Potentiometer, 200K Dual-Slide	RP50160-285	2.75
R134, 135, 136, 137	330K	RF25DC334J	.30
R140, 141, 142, 143	1.2M	RF25DC125J	.30
R144, 145, 146, 147	4.7K	RF25DC472J	.30
S81	Switch, MODE/MONITOR	SR4094-154	6.75
--	Connector, 6-Pin Male	HH20685-6	.50
--	Connector, 6-Pin Female	HH20683-6	.45

Resistors are Deposited Film, 5%, 1/4W. K=Kilohm M=Megohm